

ring中的service之间如何调用 PDF转换可能丢失图片或格式，  
建议阅读原文

[https://www.100test.com/kao\\_ti2020/255/2021\\_2022\\_ring\\_E4\\_B8\\_AD\\_E7\\_9A\\_84\\_c67\\_255778.htm](https://www.100test.com/kao_ti2020/255/2021_2022_ring_E4_B8_AD_E7_9A_84_c67_255778.htm) 在基于struts spring hibernate的开发框架下，一般service都是直接通过在Struts的action中getBean("yourServiceName")来获取，那么如果在serviceA中想调用serviceB中的方法该如何呢？直接new 一个serviceB是不行的，因为里面可能还有依赖注入的dao等其他本来需要容器管理的资源，可以象在action中一样getBean()么？获

得applicationContext就可以了：

```
ApplicationContext : public class
ApplicationContext { private static ApplicationContext applicationContext.
public static ApplicationContext getApplicationContext() { return
applicationContext. } public static void setApplicationContext(
ApplicationContext applicationContext) {
ApplicationContext.applicationContext = applicationContext.
}}SpringService : public class SpringBeanService { private static
SpringBeanService instance. private ApplicationContext
applicationContext. public static synchronized SpringBeanService
getInstance() { if (instance == null) { instance = new
SpringBeanService(). } return instance. } public ApplicationContext
getApplicationContext() { return this.applicationContext. } public
void setApplicationContext(ApplicationContext
applicationContext) { this.applicationContext = applicationContext.
} public UserService getUserService(){ return
(UserService)ApplicationContext.getApplicationContext().getBean("userS
ervice"). } }ApplicationContext的初始化 : public class
```

```
ConfigLoadListener implements ServletContextListener { public
void contextInitialized(ServletContextEvent contextEvent) { try {
WebApplicationContext context
=WebApplicationContextUtils.getRequiredWebApplicationContext
(contextEvent.getServletContext()).
AppContext.setApplicationContext(context). //读配置 try {
ServletContext context2=contextEvent.getServletContext(). String
path=context2.getInitParameter("setting.properties"). InputStream
in =context2.getResourceAsStream(path). Properties properties =
new Properties(). properties.load(in).
GlobalConstant.setCmdProperties(properties). in.close(). } catch
(IOException e) { e.printStackTrace(). } } catch
(HibernateException e) { System.out.println("系统无法初始化,异
常退出"). System.out.println(e). } } public void
contextDestroyed(ServletContextEvent contextEvent) { }} 感觉有
点麻烦，有更简便的办法了么？这篇文章大家可以参考一下
，和本文有类似之处： Struts调用Spring服务类的三种方法
100Test 下载频道开通，各类考试题目直接下载。详细请访问
www.100test.com
```